

EasyGetWifi

Wireless Fiber End-face Inspector



续航 5Hrs

Battery duration up to 5 hours

EasyGetWiFi has a USB Type C port to recharge the removable battery. It can work with re-chargers for smartphone, laptop and tablet. USB port of computer and portable battery can also be used to charge the visual inspector. The battery duration is up to 5 hours. The battery can be recharged on-line or individually.

Flexible long-distance image transfer

In WiFi mode, EasyGetWiFi can transfer the fiber end-face image to various display terminals. One-hand operation and slim body design enable EasyGetWiFi for the most complicated testing scenario. Click one button, operator can capture the fiber end-face image and save it in display terminals. Besides the WiFi mode, the inspector also supports USB mode on communication and image transmission.





Quick installation

Scan the bar-code on EasyGetWiFi to download and install the App. The App is available on mainstream App market. The user interface is simple and easy.

User-friendly design with build-in illumination

The unique focus ring and image capture scheme make the fiber end-face inspection easier, even operating with one hand. The build-in LED illuminator helps the operator to complete the measurement even when the ambient brightness level is low.



Comprehensive options for adaptors

More than 40 types of adaptors are ready for your special inspections. From standard single channel connectors to MPO, you can find the adaptor ready for your testing. The adaptors come with a special designed case for better protection in the field application.

Wide OS compatibility

EasyGetWiFi is compatible with Windows, Android, iOS and Linux system. You can use PC, tablet or smartphone to communicate with the visual inspector.



Specifications

Item	Parameter	Item	Parameter
Magnification	10X	Communication Port	WiFi802.11 and USB2.0
Video Format	MJPEG	OS Compatibility	Android 4.2/ iOS 9.3/PC Win7 /Linux2.6 or higher
View Scope	512um*384um	Power	Build-in Polymer Lithium Battery
Focus	Manual	Power Adaptor	DC 5V/2A
Power Consumption	2.0W	Charging Time	2.5H
Operational Temperature	-10°C~+50°C	Battery Duration	5H
Storage Temperature	-20°C~+50°C	Weight	188G